


# AC2751



## AS-Interface PCB module

PCB 4DI 3DO T W A/B



### Application

Application housing for panel mounting

### Electrical data

Operating voltage [V]	18...31.6 DC
Max. current consumption from AS-i [mA]	180; (without sensors: < 30 mA; inputs and outputs active: < 180 mA)
Protection class	III
Max. current load total [A]	0.15; (total current for all inputs and outputs supplied from AS-i: 150 mA)
Integrated watchdog	yes

### Inputs / outputs

Number of inputs and outputs Number of digital inputs: 4; Number of digital outputs: 3

### Inputs

Number of digital inputs	4
Input circuit of digital inputs	PNP
Sensor supply of the inputs	AS-i
Voltage supply [V]	18...30; (DC)
Max. total current rating of inputs [mA]	150
Input current High [mA]	6...10
Input current Low [mA]	0...2
Min. switching level high signal [V]	11
Digital inputs protected against short circuits	yes

### Outputs

Electrical design	PNP
Number of digital outputs	3
Circuit	PNP
Voltage range DC [V]	18...30; (DC)
Max. current load per output [mA]	100; (utilisation category DC-13 (control of electromagnets): 2,5 W (IEC 60947-5-1))
Max. current load outputs total [A]	0.15
Short-circuit proof	yes
Electrically separated	yes
Actuator supply outputs	AS-i

# AC2751



## AS-Interface PCB module

PCB 4DI 3DO T W A/B

Operating conditions		
Ambient temperature	[°C]	-25...55
Protection		IP 20
Tests / approvals		
EMC		EN 50295
MTTF	[years]	315
AS-i classification		
AS-i version		3.0
Extended addressing mode		yes
AS-i profile		S-7.A.E
AS-i I/O configuration	[hex]	7
AS-i ID code	[hex]	A.E
AS-i certificate		102401
Mechanical data		
Weight	[g]	72.5
Type of mounting		installation in a surface-mounted housing
Dimensions	[mm]	31.1 x 12 x 76.6
Materials		housing: PC potted
Displays / operating elements		
Display	operation	LED, green
	errors	LED, red
	function	LED, yellow
Remarks		
Remarks	A watchdog function switches the outputs off if there is no communication on the AS-i line.	
	Install the unit so that exposed parts cannot be touched.	
	Installation in a surface-mounted housing with the dimensions of 68 x 136 x 53 mm (LxWxH), e.g. Schneider Electric Harmony, XALD03, XALD04	
	Do not connect any of the following points to an external potential: 0-, I+, I1, I2, I3, I4	
	The connections are electrically connected with the AS-i cable. can be used up to a height of 2000 metres above sea level	
Pack quantity		1 pcs.

# AC2751



## AS-Interface PCB module

PCB 4DI 3DO T W A/B

### Electrical connection

Cable: 0.2 m, PVC;, PVC

I1 WH	switching input sensor 1
I2 WH	switching input sensor 2
I3 WH	switching input sensor 3
I4 WH	switching input sensor 4
O1 YE	switching output actuator 1
O2 YE	switching output actuator 2
O3 YE	switching output actuator 3
0- BK	sensor and actuator supply 0 V
I+ RD	sensor and actuator supply 24 V
AS-i - (FLT) BU	AS-i -
AS-i + (PWR) BN	AS-i +