

# Product data sheet

## Characteristics

# TSXCANCD300

CANopen cable - for harsh environment - IP20 - 300 m

Product availability : Stock - Normally stocked in distribution facility

Price\* : 1642.05 USD



### Main

|                                       |                        |
|---------------------------------------|------------------------|
| Range of product                      | CANopen                |
| Bus type                              | CANopen                |
| Accessory / separate part category    | Connection accessories |
| Accessory / separate part type        | Connecting cable       |
| Accessory / separate part destination | CANopen bus            |
| Cable length                          | 984.25 ft (300 m)      |

### Complementary

|                |                        |
|----------------|------------------------|
| Marking        | CE                     |
| Product weight | 47.84 lb(US) (21.7 kg) |

### Environment

|                         |      |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

### Ordering and shipping details

|                       |                                       |
|-----------------------|---------------------------------------|
| Category              | 22558 - TSX PREMIUM, ATRIUM & PL7 PRO |
| Discount Schedule     | PC22                                  |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 47.800000000000004                    |
| Returnability         | N                                     |
| Country of origin     | IT                                    |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 1005 - Schneider Electric declaration of conformity |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

---