

# Product data sheet

## Characteristics

# TSXP57554MC

Unity processor - 8 racks (12 slots)/16 racks (4/6/8 slots) - 1680 mA 5 V DC

Product availability : Non-Stock - Not normally stocked in distribution facility

Price\* : 15,327.20 USD



⚠ Discontinued

### Main

Range of product	Modicon Premium Automation platform
Product or component type	Unity processor
Software designation	Unity Pro

### Complementary

Number of racks	16 4/6/8 slots 8 12 slots
Number of slots	128 96 64
Discrete I/O processor capacity	2040 I/O
Analogue I/O processor capacity	512 I/O
Number of application specific channel	64
Number of process control channel	30 up to 90 simple loops
Integrated connection type	Non isolated serial link female mini DIN RS485)19.2 kbit/s) Fipio manager (127 agents) SUB-D 9 USB port12 Mbit/s)
Communication module processor capacity	4 1 8 5
Memory description	Internal RAM (with PCMCIA card) 1024 kB data Internal RAM (with PCMCIA card) 7168 kB program Internal RAM (without PCMCIA card) 1024 kB program and data PCMCIA card 16384 kB additional data storage
Maximum size of object areas	128 %MWi internal words located internal data 32768 %Mi located internal bits 64 %KWi constant words located internal data Unlimited (DFB and EFB function blocks) unlocated internal data Unlimited (elementary and derived data) unlocated internal data
Application structure	4 auxiliary tasks 32 timers 1 master task 1 fast task 128 event tasks

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Execution time per instruction	0.0375...0.045 $\mu$ s Boolean with PCMCIA card 0.0375...0.045 $\mu$ s Boolean without PCMCIA card 0.045...0.06 $\mu$ s word or fixed-point arithmetic with PCMCIA card 0.045...0.06 $\mu$ s word or fixed-point arithmetic without PCMCIA card 0.48...0.56 $\mu$ s floating points with PCMCIA card 0.48...0.56 $\mu$ s floating points without PCMCIA card
Number of instructions per ms	14 Kinst/ms 65 % Boolean + 35 % fixed arithmetic with PCMCIA card 14 Kinst/ms 65 % Boolean + 35 % fixed arithmetic without PCMCIA card 20.26 Kinst/ms 100 % Boolean with PCMCIA card 20.26 Kinst/ms 100 % Boolean without PCMCIA card
System overhead	0.07 ms fast task 1 ms master task
Marking	CE
Local signalling	for processor running (RUN) 1 LED (green) for activity on Fipio bus (FIP) 1 LED (red) for I/O module or configuration fault (I/O) 1 LED (red) for processor or system fault (ERR) 1 LED (red) for activity on TER or AUX terminal port (TER) 1 LED (yellow)
Current consumption	1680 mA 5 V DC
Module format	Double
Net Weight	1.23 lb(US) (0.56 kg)

## Environment

Standards	CSA C22.2 No 213 Class I Division 2 Group C CSA C22.2 No 142 89/336/EEC CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group D 93/68/EEC IEC 61131-2 UL 508 92/31/EEC 73/23/EEC CSA C22.2 No 213 Class I Division 2 Group A
Product certifications	DNV RMRS RINA LR BV GL ABS
Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-13...158 °F (-25...70 °C)
Relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
Operating altitude	0...6561.68 ft (0...2000 m)
Protective treatment	TC Conformal coating Humiseal 1A33
IP degree of protection	IP20
Pollution degree	2

## Ordering and shipping details

Category	22558 - TSX PREMIUM, ATRIUM & PL7 PRO
Discount Schedule	PC22
GTIN	03595863944181
Nbr. of units in pkg.	1
Package weight(Lbs)	2.2 lb(US) (1.00 kg)
Returnability	No
Country of origin	FR

### Packing Units

Package 1 Height	3.74 in (95.000 mm)
Package 1 width	7.09 in (180.000 mm)
Package 1 Length	10.24 in (260.000 mm)

### Contractual warranty

Warranty	18 months
----------	-----------