



Figure similar

\*\*\*Spare part\*\*\* SIMATIC S7-200, Digital I/O EM 223, only for S7-22X CPU, 16 DI 24 V DC, Sink/Source, 16DO 24 V DC; 0.75 A/channel,source

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>permissible range, lower limit (DC)</li> </ul>	20.4 V
<ul style="list-style-type: none"> <li>permissible range, upper limit (DC)</li> </ul>	28.8 V
Input current	
from backplane bus 5 V DC, max.	160 mA
Power loss	
Power loss, typ.	6 W
Digital inputs	
Number of digital inputs	16
Input voltage	
<ul style="list-style-type: none"> <li>Type of input voltage</li> </ul>	DC
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>for signal "0"</li> </ul>	0 to 5 V
<ul style="list-style-type: none"> <li>for signal "1"</li> </ul>	15 V DC to 30 V DC
Input current	
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	4.5 ms
Digital outputs	
Number of digital outputs	16
Short-circuit protection	No
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output voltage	
<ul style="list-style-type: none"> <li>for signal "0", max.</li> </ul>	0.1 V
Output current	
<ul style="list-style-type: none"> <li>for signal "1" rated value</li> </ul>	750 mA
Total current of the outputs (per group)	
all mounting positions	
— Current per conductor/group, max.	3 A
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	0.75 A; each output
— on lamp load, max.	5 W

— with resistive load, max.	0.75 A; each output
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	150 m
<b>Encoder</b>	
<b>Connectable encoders</b>	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
• Potential separation digital inputs	Yes; Optocoupler
• between the channels, in groups of	4
<b>Potential separation digital outputs</b>	
• Potential separation digital outputs	Yes; Optocoupler
• between the channels, in groups of	4
<b>Isolation</b>	
Isolation tested with	500 V AC
<b>Connection method</b>	
Plug-in I/O terminals	Yes
<b>Dimensions</b>	
Width	137.5 mm
Height	80 mm
Depth	62 mm
<b>Weights</b>	
Weight, approx.	360 g
<b>last modified:</b>	4/8/2020 