



SIMATIC DP, ET 200ECO PN, 8 DI 24 V DC; 4xM12, Duplicate assignment, Degree of protection IP67

General information	
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	Yes
Input current	
Current consumption, typ.	100 mA
from supply voltage 1L+, max.	4 A
Encoder supply	
Number of outputs	4
24 V encoder supply	
<ul style="list-style-type: none"> Short-circuit protection Output current, max. 	Yes; Electronic 100 mA; per output
Power loss	
Power loss, typ.	5.5 W
Digital inputs	
Number of digital inputs	8
<ul style="list-style-type: none"> in groups of 	2
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 60 °C, max.	8
Input voltage	
<ul style="list-style-type: none"> Rated value (DC) for signal "0" for signal "1" 	24 V -3 to +5V +11 to +30V
Input current	
<ul style="list-style-type: none"> for signal "1", typ. 	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	typically 3 ms
— at "1" to "0", max.	typically 3 ms
Cable length	
<ul style="list-style-type: none"> unshielded, max. 	30 m
Encoder	
Connectable encoders	

- 2-wire sensor
- permissible quiescent current (2-wire sensor), max.

Yes
1.5 mA

Interfaces

Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1

1. Interface

Interface types

- M12 port
- integrated switch

Yes
Yes

Interface types

M12 port

- Autonegotiation
- Autocrossing
- Transmission rate, max.

Yes
Yes
100 Mbit/s

Protocols

Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
PROFIsafe	No

PROFINET IO Device

Services

- IRT with the option "high flexibility"
- Prioritized startup

Yes
Yes

Redundancy mode

Media redundancy

- MRP

Yes

Open IE communication

- TCP/IP
- SNMP
- DCP
- LLDP
- ping
- ARP

No
Yes
Yes
Yes
Yes
Yes

Interrupts/diagnostics/status information

Diagnostics function	Yes
----------------------	-----

Alarms

- Diagnostic alarm

Yes

Diagnoses

- Diagnostic information readable
- Monitoring the supply voltage
- Wire-break in signal transmitter cable
- Short-circuit encoder supply
- Group error

Yes
Yes; green "ON" LED
Yes
Yes; Per channel group
Yes; Red/yellow "SF/MT" LED

Potential separation

between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes

Potential separation channels

- between the channels

No

Isolation

tested with

- 24 V DC circuits
- Test voltage for interface, rms value [Vrms]

707 V DC (type test)
1 500 V; According to IEEE 802.3

Degree and class of protection

IP degree of protection	IP65/67
-------------------------	---------

connection method / header

Design of electrical connection	4/5-pin M12 circular connectors
---------------------------------	---------------------------------

Dimensions

Width	30 mm
-------	-------

Height	200 mm
Depth	49 mm
Weights	
Weight, approx.	550 g
last modified:	10/25/2021 