

product type designation

PROFIBUS bus terminal 12M

Bus terminal 12M for PROFIBUS, transfer rates 9.6 Kbit/s to 12 Mbit/s, plug-in cable 1.5 m .



transfer rate	
transfer rate	
<ul style="list-style-type: none"> with PROFIBUS 	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of electrical connections	
<ul style="list-style-type: none"> for PROFIBUS cables 	2
type of electrical connection	
<ul style="list-style-type: none"> for PROFIBUS cables 	Screw terminals
mechanical data	
material / of the enclosure	plastic
design, dimensions and weights	
width	50 mm
height	138 mm
depth	53 mm
net weight	360 g
fastening method	
<ul style="list-style-type: none"> 35 mm top hat DIN rail mounting 	Yes
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> silicon-free 	Yes
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> UL approval 	Yes
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified:

6/30/2021